

Microinverter Datasheet

HMS-1600-4T
HMS-1800-4T
HMS-2000-4T

Description

With the output power up to 2000 VA, Hoymiles new microinverter HMS-2000 series rank among the highest for 4-in-1 microinverters.

Each microinverter can connect up to 4 panels, with independent MPPT and monitoring maximizing the power production of your installation.

The new Sub-1G wireless solution enables more stable communication with Hoymiles gateway DTU.

Features

01 High-powered microinverter with output power up to 2000 VA

02 Independent MPPT and monitoring ensure greater energy harvest and easier maintenance

03 With Reactive Power Control, compliant with VDE-AR-N 4105:2018, IEC 61727, IEC 62116, etc.

04 4-in-1 design enables faster installation and comes with a lower cost

05 Safer for rooftop solar stations with rapid shutdown compliance and isolated transformer

06 Sub-1G wireless solution allows stable communication in commercial and industrial settings

© 2024 Hoymiles Power Electronics Inc. All rights reserved.
hoymiles.com
sales@hoymiles.com

Technical Specifications

Model	HMS-1600-4T			HMS-1800-4T			HMS-2000-4T		
Input Data (DC)									
Commonly used module power (W)	320 to 540+			360 to 600+			400 to 670+		
Maximum input voltage (V)	65								
MPPT voltage range (V)	16–60								
Start-up voltage (V)	22								
Maximum input current (A)	4 × 14			4 × 15			4 × 16		
Maximum input short circuit current (A)	4 × 25								
Number of MPPTs	4								
Number of inputs per MPPT	1								
Output Data (AC)									
Rated output power (VA)	1600			1800			2000		
Rated output current (A)	7.27	6.96	6.67	8.18	7.83	7.50	9.09	8.70	8.33
Nominal output voltage/range (V)*	220/180–275	230/180–275	240/180–275	220/180–275	230/180–275	240/180–275	220/180–275	230/180–275	240/180–275
Nominal frequency/range (Hz)*	50/45–55 or 60/55–65								
Adjustable power factor (@nominal power)	> 0.99 default 0.8 leading ... 0.8 lagging								
Total harmonic distortion (@nominal power)	< 3%								
Maximum units per 6 mm² line**	5	5	6	4	5	5	4	4	4
Efficiency									
CEC peak efficiency	96.70%			96.50%			96.50%		
Nominal MPPT efficiency	99.80%								
Night power consumption (mW)	< 50								
Mechanical Data									
Ambient temperature range (°C)	-40 to +65								
Dimensions (W × H × D [mm])	331 × 218 × 40.6								
Weight (kg)	5.56								
Enclosure rating	Outdoor-IP67								
Cooling	Natural convection-No fans								
Features									
Communication	Sub-1G								
Type of isolation	Galvanically Isolated HF Transformer								
Monitoring	S-Miles Cloud (Hoymiles Monitoring Platform)								
Compliance	EN 50549-1: 2019, VDE-AR-N 4105: 2018, UL 1741, IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4, IEC/EN 61000-3-2/-3, IEC 61727, IEC 62116, IEC 61683, IEC60068-2-1/-2/-14/-30, IEC 62920								

* : Nominal voltage/frequency range can vary depending on local requirements.
**: Refer to local requirements for exact number of microinverters per AC output line.

© 2024 Hoymiles Power Electronics Inc. All rights reserved.