GOODWE

ES Series

5kW I Single Phase I Hybrid Inverter

The GoodWe ES series of bi-directional energy storage inverters can be used for both on-grid and off-grid PV systems, with the ability to control the flow of energy intelligently. During the day, the PV array generates electricity which can be provided either to the loads, fed into the grid, or charge the battery, depending on the economics and set-up. The electricity stored can be released when the loads require it during the night, including inductive loads such as air conditioners or refrigerators. Additionally, the power grid can also charge storage devices via the inverter. An all-round intelligent system for maximum energy flexibility.



- Charge controller and inverter integrated
- Maximum charge and discharge up to 100A
- Export control (Zero export)
- IP65 dustproof and waterproof
- <10ms UPS-level Switching
- Fanless design, long lifespan

GOODWE

Technical Data	GW3648D-ES[*7] GW3648C-ES[*7]	GW5048D-ES[*8] GW5048C-ES[*8]
Battery Input Data		
Battery Type	Li-Ion	
Nominal Battery Voltage (V)	48	
Max. Continuous Charging Current (A)[*1]	75	100
Max. Continuous Discharging Current (A)[*1]	75	100
PV String Input Data		
Max. Input Power (W)	4950	6700
Max. Input Voltage (V)	580	
MPPT Operating Voltage Range (V)[**]	125 ~ 550	
Start-up Voltage (V)	125	
Nominal Input Voltage (V)	360	
Max. Input Current per MPPT (A)	11 / 11	
Max. Short Circuit Current per MPPT (A)[*9]	13.8 / 13.8	
Number of MPP Trackers	2	
Number of Strings per MPPT	1	
AC Output Data (On-grid)		
Nominal Apparent Power Output to Utility Grid (VA)[*5]	3680	5000
Max. Apparent Power Output to Utility Grid (VA)[*2]	3680	5000
Max. Apparent Power from Utility Grid (VA)	7360	9200
Nominal Output Voltage (V)	230	
Nominal AC Grid Frequency (Hz)	50 / 60	
Max. AC Current Output to Utility Grid (A)	16.0[*6]	24.5
Max. AC Current From Utility Grid (A)	32	40
Power Factor	~1 (Adjustable from 0.8 leading to 0.8 lagging)	
Max. Total Harmonic Distortion	<3%	
AC Output Data (Back-up)		
Back-up Nominal Apparent Power (VA)	3680	4600
Max. Output Apparent Power (VA)[*3]	3680	4600
Max. Output Current (A)	16	20
Nominal Output Voltage (V)	230 (± 2%)	
Nominal Output Frequency (Hz)	50 / 60 (± 0.2%)	
Output THDv (@Linear Load)	<3%	
Efficiency		
Max. Efficiency	97.6%	
European Efficiency	97.0%	
Max. Battery to AC Efficiency	94.0%	
MPPT Efficiency	99.9%	
Protection		
PV Insulation Resistance Detection	Integrated	
Residual Current Monitoring	Integrated	
PV Reverse Polarity Protection	Integrated	
Anti-islanding Protection	Integrated	
AC Overcurrent Protection	Integrated	
AC Short Circuit Protection	Integrated	
AC Overvoltage Protection	Integrated	
General Data		
Operating Temperature Range (°C)	-25 ~ +60	
Relative Humidity	0 ~ 95%	
Max. Operating Altitude (m)	3000	
Cooling Method	Natural Convection	
Display	LED & APP	
Communication with BMS[*4]	RS485; CAN	
Communication with Meter	RS485	
Communication with Portal	Wi-Fi	
Weight (kg)	28	30
Dimension (W × H × D mm)	516 × 440 × 184	
Noise Emission (dB)	<25	
Topology	Battery Isolation	
Self-consumption at Night (W)	<13	
Ingress Protection Rating	IP65	
Mounting Method	Wall Bracket	
Country of Manufacture	China	

*1: The actual charge and discharge current also depends on the battery.
*2: 4600 for VDE 0126-1-1 & VDE-AR-N4105 & NRS 097-2-1, 5100 for CEI 0-21 (GW5048D-ES); 4050 for CEI 0-21 (GW3648D-ES).
*3: Peak output apparent power can be reached only if PV and battery power is enough.
*4: CAN communication is configured by default. If 485 communication is used, please replace the corresponding communication line.
*5: 4600 for VDE 0126-1-1 &VDE-AR-N4105 &NRS 097-2-1, 4600 for CEI 0-21 (GW5048D-ES).
*6: 18 for CEI 0-21.
*7: FOR AUSTRALIA ONLY. Model GW3648D-ES inverters are designed without DC switch. For inverters designed with DC switch, the model name should be GW3648C-ES.
*8: FOR AUSTRALIA ONLY. Model GW5048D-ES inverters are designed without DC switch. For inverters designed with DC switch, the model name should be GW5048C-ES.
*9: For Australia Max. Short Circuit Current per MPPT (A) please refer to 'Manufacturer declaration: short circuit current'.
*: Under off-grid mode, then battery capacity should be more than 100Ah.
*: When there is no battery connected, inverter starts feeding in only if string voltage is higher than 200V.
*: Please visit GoodWe website for the latest certificates.
**: Please refer to the user manual for the MPPT Voltage Range at Nominal Power.

GoodWe-Single page-20250417-AU-V2.1. Information may be subject to change without notice during product improving.