HIONE - THREE-PHASE INVERTER

HiOne-(8-20)T-G3-AU



Features

Slimmer

Integrates the inverter, battery, and EMS into one compact stackable system, reducing the overall footprint compared to separate components.

Faster

Plug-and-play connections and a stackable design enable installation within 15 minutes.

Stronger

Supports flexible system design with up to 4 MPPTs and up to 20 A input current, while enabling mix-and-match battery expansion up to 64 kWh per system.

Technical Specifications

Model	HiOne-8T-G3-AU	HiOne-10T-G3-AU	HiOne-12T-G3-AU	HiOne-16T-G3-AU	HiOne-20T-G3-AU
Battery					
Battery type	Li-ion				
Battery voltage rangve (V)	720-950				
Compatible battery model	HiOne-8B-G3				
Number of modules	1-8[1]				
PV Input					
Recommended max. PV power (W)	16000	20000	24000	32000	40000
Max. input voltage (V)	1000				
Rated voltage (V)	720				
Start-up voltage (V)	170				
MPPT voltage range (V)	150-950				
Max. input current (A)	20/20/20	20/20/20	20/20/20/20	20/20/20/20	20/20/20/20
Max. short circuit current (A)	30/30/30	30/30/30	30/30/30/30	30/30/30/30	30/30/30/30
MPPT number / Max. input strings number	3/3	3/3	4/4	4/4	4/4
AC Output					
Rated output power (W)	8000	9900	12000	16000	20000
Max. on-grid output apparent power (VA)	8800	9900	13200	17600	22000
Max. output current (A)[2]	13.3	14.3	20.0	26.7	33.3
Max. off-grid output apparent power (VA)[3]	12000 (10 s)	15000 (10 s)	18000 (10 s)	24000 (10 s)	30000 (10 s)
Grid form	3L/N/PE				
Nominal AC output voltage (V)	220/380, 230/400				
Nominal grid frequency (Hz)	50/60				
Power factor	>0.99 (0.8 leading-0.8 lagging)				
THDi (@rated output)	<3%				
Efficiency					
Max. efficiency	98.5%				
EU efficiency	98.0%				
Protection					
Anti-islanding protection	Integrated				
PV string input reverse polarity protection	Integrated				
Insulation resistor detection	Integrated				
Residual current monitoring unit	Integrated				
AC overcurrent protection	Integrated				
AC short circuit protection	Integrated				
AC overvoltage and undervoltage protection	Integrated				
Surge protection	DC Type II / AC Type II				
General					
Dimensions (W × H × D [mm])	620 × 360 × 255				
Weight (kg)	31				
Mounting	Floor-standing / Wall-mounting (optional)				
Operating temperature (°C)	-30 to +65 (>45, derating)				
Relative humidity	0-100%				
Cooling	Natural convection	Natural convection	Intelligent air cooling	Intelligent air cooling	Intelligent air cooling
Topology (Solar/Battery)	Transformerless/High-frequency isolation				
Altitude (m)	≤4000				
Protection degree	IP66				
User interface	LED & App				
Communication	RS485, Bluetooth/Wi-Fi/WL/4G (optional)				
Warranty[4]	10 years				

(1) Up to four modules can be stacked in one battery tower.
(2) The value is calculated based on a voltage of 230 V.
(3) Applicable only when the inverter is connected to Hoymiles gateway.
(4) For specific warranty policies, please refer to the relevant warranty documents.

© 2026 Hoymiles Power Electronics Inc. All rights reserved.

HIONE - BATTERY

HiOne-8B-G3



Features

01 Equipped with 314 Ah large-capacity cells for extended cycle life and enduring performance

02 Multi-layer protection mechanisms ensure comprehensive electrical safety

03 Built-in optimizers support mixed use of new and old battery packs, maximizing system scalability

04 Adapts to low temperature with self-heating technology, ensuring performance even in extreme cold

Technical Specifications

Model	HiOne-8B-G3
Battery Data	
Battery type	$LiFePO_4$
Cell capacity (Ah)	314
Cycle life	8000(1)
Total energy (kWh)	8
Usable energy (kWh)	7.8(2)
Depth of discharge	100%(3)
Max. charging/discharging power (kW)	4
Peak discharge power (kW)	6 (10 s)
Max. stackable quantity	4
Max. parallel quantity	2
General	
Dimensions (W × H × D [mm])	620 × 360 × 255 (single pack)
Weight (kg)	67
Mounting	Wall-mounting / Floor-standing
Installation environment	Indoor / Outdoor
Storage temperature range (°C)	-25 to +60
Charging/discharging temperature range (°C)	-20 to +55
Protection degree	IP66
Cooling	Natural convection
Altitude (m)	≤4000
Relative humidity range	5% - 95%
Compatible inverters	HiOne-(8-20)T-G3-AU, HiOne-(3.6-12)S-G3-AU
Warranty(4)	10 Years

(1) This value is provided by the cell manufacturer and is based on the following conditions: SOH=70%, 0.5 C charge/discharge rate at 25±2°C.
(2) This value is measured at the beginning of life under the following conditions: 100% depth of discharge, 0.2 C charge/discharge rate at 25±2°C.
(3) This value refers to the usable energy capacity of the battery. To keep the battery in good condition, recharge it within 7 days after it has been fully discharged.
(4) For specific warranty policies, please refer to the relevant warranty documents.



© 2026 Hoymiles Power Electronics Inc. All rights reserved.