GOODWE



Smart and scalable residential all-in-one energy storage solution

- Fast, hassle-free and lower cost installation
- Scalable and flexible solution
- Highest safety and optimized performance
- Smart, Seamless Energy Management

The GoodWe ESA Series is an all-in-one residential energy storage solution (ESS) that combines reliability and advanced functionality. It integrates the inverter, battery, UPS-grade switching, and battery enclosure in a pre-wired modular system-streamlining installation and reducing costs.

Compact, elegantly designed, and IP66-rated for durability, the unit operates reliably indoors or outdoors in any weather conditions. With smart controls, scalable storage, and flexible configurations, the ESA empowers homeowners to manage their energy needs with confidence and ease.

The innovative modular and stackable design ensures adaptability, growing alongside your household energy demands and making true energy independence simpler than ever.



- AI-driven EMS and <4ms UPS-level switching
- Smart home integration with multi-protocol communications
- Allows different capacities of old and new batteries mixing
- Supports 6 batteries per stack, scalable up to 54kWh

ESA Series / Power Module

GOODWE

Technical Data	GW3K-EHA-G20	GW3.6K-EHA-G20	GW5K-EHA-G20	GW5.75K-EHA-G20*6	GW6K-EHA-G20	GW8K-EHA-G20	GW10K-EHA-G20
Battery Side							
Battery Type				$LiFePO_4$			
Nominal Battery Voltage (V)				380			
Battery Voltage Range (V)				350 ~ 550			
Start-up Voltage (V)*1				380			
Number of Battery Input				1			
Max. Continuous Charging Current (A)	11.9	14.3	19.8	23.7	23.7	31.6	35.6
Max. Continuous Discharging Current (A)	8.7	10.5	14.5	17.4	17.4	23.2	29.0
Max. Charging Power (kW)	4.5	5.4	7.5	9.0	9.0	12.0	13.5
Max. Discharging Power (kW)	3.3	3.96	5.5	6.6	6.6	8.8	11.0
PV Side							
Max. Input Power (kW)	6.0	7.2	10.0	11.5	12.0	16.0	20.0
Max. Input Voltage (V)*2				600			
MPPT Operating Voltage Range (V)*3				40 ~ 560			
Start-up Voltage (V)				50			
Nominal Input Voltage (V)				400			
Max. MPPT Current (A)				20			
Max. MPPT Short Circuit Current (A)				26			
Number of MPPTs	2	2	2	2	2	4	4
Number of Strings per MPPT	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1 / 1 / 1	1 / 1 / 1 / 1
AC Side (On-grid)							
Nominal Power (kW)	3.0	3.6	5.0	5.75	6.0	8.0	10.0
Nominal Apparent Power to Grid (kVA)	3.0	3.6	5.0	5.75	6.0	8.0	10.0
Max. Apparent Power to Grid (kVA)	3.0	3.6	5.0	5.75	6.0	8.0	10.0
Max. Apparent Power from Grid (kVA)*4	6.0	7.2	10.0	11.5	12.0	14.5	14.5
Nominal Voltage (V)	220 / 230 / 240, L / N / PE			230, L / N / PE	220 / 230 / 240, L / N / PE		
Voltage Range (V)				170 ~ 280			
Nominal Frequency (Hz)				50 / 60			
Frequency Range (Hz)				45 ~ 55 / 55 ~ 65			
Max. Current to Grid (A)	13.7 @ 220V 13.1 @ 230V 12.5 @ 240V	16.4 @ 220V 15.7 @ 230V 15.0 @ 240V	22.8 @ 220V 21.8 @ 230V 20.9 @ 240V	25 @ 230V	27.3 @ 220V 26.1 @ 230V 25.0 @ 240V	36.4 @ 220V 34.8 @ 230V 33.4 @ 240V	43.5 @ 220V 43.5 @ 230V 41.7 @ 240V
Max. Current From Grid (A)*4	27.3 @ 220V 26.1 @ 230V 25.0 @ 240V	32.8 @ 220V 31.4 @ 230V 30.0 @ 240V	45.5 @ 220V 43.5 @ 230V 41.7 @ 240V	50 @ 230V	50.0 @ 220V 50.0 @ 230V 50.0 @ 240V	63.0 @ 220V 63.0 @ 230V 60.5 @ 240V	63.0 @ 220V 63.0 @ 230V 60.5 @ 240V
Power Factor	~1 (Adjustable from 0.8 leading to 0.8 lagging)						
THDi	<3%						
Back-up Side							
Nominal Output Apparent Power (kVA)	3.0	3.6	5.0	5.75	6.0	8.0	10.0
Max. Output Apparent Power (kVA)	3.0 (6.0, 10s)	3.6 (7.2, 10s)	5.0 (10.0, 10s)	5.75 (11.5, 10s)	6.0 (12.0, 10s)	8.0 (16.0, 10s)	10.0 (20.0, 10s)
Max. Output Apparent Power (Bypass) (kVA)	6.0	7.2	10.0	11.5	12.0	14.5	14.5
Max. Output Current (A)*5	13.7 @ 220V 13.1 @ 230V 12.5 @ 240V	16.4 @ 220V 15.7 @ 230V 15.0 @ 240V	22.8 @ 220V 21.8 @ 230V 20.9 @ 240V	25 @ 230V	27.3 @ 220V 26.1 @ 230V 25.0 @ 240V	36.4 @ 220V 34.8 @ 230V 33.4 @ 240V	43.5 @ 220V 43.5 @ 230V 41.7 @ 240V
Max. Output Current (Bypass) (A)*5	27.3	32.8	45.5	50	50.0	63.0	63.0
Nominal Output Voltage (V)	220 / 230 / 240, L / N / PE						
Nominal Output Frequency (Hz)	50 / 60						
THDv (@Linear Load)	<3%						
Efficiency							
Max. Efficiency	97.6%	97.6%	97.6%	97.6%	97.6%	97.5%	97.5%
European Efficiency	96.5%	96.5%	96.8%	97.0%	97.0%	96.8%	96.8%
Max. Battery to AC Efficiency	98.0%	98.0%	98.0%	98.0%	98.0%	97.8%	97.8%
Protection							
PV String Current Monitoring	Integrated						
PV Insulation Resistance Detection	Integrated						
Residual Current Monitoring	Integrated						
PV Reverse Polarity Protection	Integrated						
Battery Reverse Polarity Protection	Integrated						
Anti-islanding Protection	Integrated						
AC Overcurrent Protection	Integrated						
AC Short Circuit Protection	Integrated						
AC Overvoltage Protection	Integrated						
DC Surge Protection	Type II						
AC Surge Protection	Type II						
RSD	Optional						
AFCI	Integrated						
Remote Shutdown	Integrated						
General Data							
Operating Temperature Range (°C)	-35 ~ +60 (Derating at +40)						
Relative Humidity	0 ~ 95%						
Max. Operating Altitude (m)	4000 (>2000 derating)						
Cooling Method	Natural convection						
User Interface	LED, WLAN + APP						
Communication with BMS	CAN						
Communication	RS485, WiFI + LAN + Bluetooth ,4G + Bluetooth (Optional)						
Communication Protocols	Modbus-RTU, Modbus-TCP						
Weight (kg)	24	24	24		24	26	26
Dimension (W × H × D mm)	800 × 300 × 270						
Noise Emission	≤30	≤30	≤30		≤30	≤35	≤35
Topology	Non-isolated						
Ingress Protection Rating	IP66						
Mounting Method	Wall / Floor Mounted						

*1: If there's no PV, start-up voltage will be 380V.
*2: When the input voltage is 560V-600V, the inverter will enter standby mode, and the voltage returns to 560V to enter the normal operation state.
*3: Please refer to the user manual for the MPPT Voltage Range at Nominal Power.
*4: GOODWE ESA series has internal bypass 63A passthrough ability to supprt whole home backup solution. If the customer don't want to do any breaker upgrade, the main breaker size in SolarGo (or SEMS+) can be set as previous breaker size.
*5: If the Back-up port is not used, select an appropriate circuit breaker based on the AC Max. Output Current.
*6: Only available in Ireland.
*: Please visit GoodWe website for the latest certificates.

GoodWe-Single page-20261026-EMEA-EN-V1.1. Information may be subject to change without notice during product improving.

This datasheet provides information about products offered in the EMEA region.

ESA Series / Battery Module*

GOODWE

Technical Data		GW5.1-BAT-D-G20	GW8.3-BAT-D-G20	GW6.0-BAT-D-G20	GW9.0-BAT-D-G20
Battery Type		LFP ($LiFePO_4$)			
Rated Energy (kWh)		5.12	8.32	6.0	9.0
Usable Energy (kWh)		5.0*1	8.0*1	5.8*2	8.7*2
Operating Voltage Range (V) (single phase system)		350 ~ 550			
Operating Voltage Range (V) (three phase system)		700 ~ 950			
Max. Input Current (System) (A)		12.0	19.0	7.1	10.7
Max. Output Current (System) (A)		13.2	21.0	7.9	11.8
Max. Input Power (System) (kW)*3		5.0	8.0	3.0	4.5
Max. Output Power (System) (kW)*3		5.0	8.0	3.0	4.5
Peak.Output Power (System) (kW)*3		7.5 @10s	12 @10s	4.5 @ 10s	6.75 @ 10s
Charging Temperature Range (°C)		-18 ~ +55	-18 ~ +55	-20 ~ +55	-20 ~ +55
Discharging Temperature Range (°C)		-20 ~ +55			
Relative Humidity		4 ~ 100%			
Max. Operating Altitude (m)		4000			
Noise Emission (dB)		≤29	≤29	≤27	≤27
Communication		CAN	CAN	CAN & 485	CAN & 485
Weight (kg)		57.5 ± 1	79 ± 1	61 ± 1	77± 1
Ingress Protection		IP66			
Dimensions (W × H × D mm)		800 × 326 × 270			
Function Configuration		Heating (Integrated); Aerosol fire extinguishing (Integrated)			
Max. Storage time		12 months (-20°C ~ +35°C) 6 months (+35°C ~ +45°C)			
Scalability*4		12 pcs			
Mounting Method		Floor stacked / Wall-mounted		Floor stacked / Wall-mounted / Grounded	
Cycle Life*5		≥8000	≥8000	≥10000	≥10000
Standard and Certification	Safety	IEC62619, IEC60730, EN62477, IEC63056, IEC62040, CE, CEC, VDE2510		IEC62619, IEC60730, EN62477, IEC63056, IEC62040, CE, CEC, Regulation 2023 / 1542, VDE2510-50	
	EMC	CE, RCM			
	Transportation	UN38.3, ADR			

*1: Test conditions, 100% DOD (cell 2.85~3.6V voltage range), 0.2P charge & discharge at 25±2°C for battery system at the beginning of life. Usable energy is defined by its initial design value. Actual available energy may vary depending on charge/discharge rate, environmental conditions (e.g. temperature), transport and storage factors.
*2: Test conditions, 100% DOD (cell 2.87~3.61V voltage range), 0.4P charge & discharge at 25±2°C for battery system at the beginning of life. Usable energy is defined by its initial design value. Actual available energy may vary depending on charge/discharge rate, environmental conditions (e.g. temperature), transport and storage factors.
*3: Max. Input Power /Max. Output Power/Peak.Output Power derating will occur related to Temperature and SOC.
*4: For single-column stacked installations, the maximum number of parallel units is 6.
*5: Based on test data under specific laboratory conditions.
*: Based on Lynx D G2 Series technology
*: Please visit GoodWe website for the latest certificates.

This datasheet provides information about products offered in the EMEA region.

Scan and follow GoodWe

Copyright © GoodWe Technologies Co., Ltd. 2026. All rights reserved.

Disclaimer

The technical data above mentioned may be modified in order to reflect continuous technical innovation and improvements achieved by GoodWe's R&D team. GoodWe has the sole right to make such modification at any time without further notice. GoodWe's customers have the right to request the latest version of GoodWe product datasheets and any commercial contracts that may be signed will be based on the most recent version of the datasheet at the moment of signing the contract.

emea.goodwe.com