


Microinverter Datasheet

HMS-1600
HMS-1800
HMS-2000

Description

With the output power up to 2000 VA, Hoymiles new microinverter HMS-2000 series rank among the highest for 4-in-1 microinverters.

All of these three models listed are equipped with reactive power control and can meet the requirements of EN 50549-1:2019, VDE-AR-N 4105:2018, UL 1741, etc.

The new Sub-1G wireless solution enables more stable communication with Hoymiles gateway DTU.

Features

01	High-powered microinverter with output power up to 2000 VA
02	Independent MPPT and monitoring ensure greater energy harvest and easier maintenance
03	With Reactive Power Control, compliant with EN 50549-1:2019, VDE-AR-N 4105:2018, UL 1741, ABNT NBR 16150, etc.
04	4-in-1 design enables faster installation and comes with a lower cost
05	Safer for rooftop solar stations with rapid shutdown compliance and isolated transformer
06	Sub-1G wireless solution allows stable communication in commercial and industrial settings

© 2021 Hoymiles Power Electronics Inc. All rights reserved.
hoymiles.com
sales@hoymiles.com

Technical Specifications

Model	HMS-1600-4T			HMS-1800-4T			HMS-2000-4T		
Input Data (DC)									
Commonly used module power (W)	320 to 500+			360 to 565+			400 to 625+		
Maximum input voltage (V)	65								
MPPT voltage range (V)	16–60								
Start-up voltage (V)	22								
Maximum input current (A)	4 × 12.5			4 × 13.3			4 × 14		
Maximum input short circuit current (A)	4 × 20								
Output Data (AC)									
Rated output power (VA)	1600			1800			2000		
Rated output current (A)	7.27	6.96	6.67	8.18	7.83	7.5	9.09	8.7	8.33
Nominal output voltage/range (V)[1]	220/180–275	230/180–275	240/180–275	220/180–275	230/180–275	240/180–275	220/180–275	230/180–275	240/180–275
Nominal frequency/range (Hz)[1]	50/45-55 or 60/55-65								
Power factor (adjustable)	> 0.99 default 0.8 leading...0.8 lagging								
Total harmonic distortion	< 3%								
Maximum units per 10AWG branch[2]	4	4	4	3	4	4	3	3	3
Efficiency									
CEC peak efficiency	96.5%								
Nominal MPPT efficiency	99.8%								
Night power consumption (mW)	< 50								
Mechanical Data									
Ambient temperature range (°C)	-40 to +65								
Dimensions (W × H × D mm)	331 × 218 × 34.6								
Weight (kg)	4.7								
Enclosure rating	Outdoor-IP67 (NEMA 6)								
Cooling	Natural convection-No fans								
Features									
Communication	Sub-1G								
Type of isolation	Galvanically Isolated HF Transformer								
Monitoring	S-Miles Cloud[3]								
Compliance	EN 50549-1: 2019, VDE-AR-N 4105: 2018, UL 1741, ABNT NBR 16150, IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4, IEC/EN 61000-3-2/-3								

*1 Nominal voltage/frequency range can vary depending on local requirements.
*2 Refer to local requirements for exact number of microinverters per branch.
*3 Hoymiles Monitoring System

© 2021 Hoymiles Power Electronics Inc. All rights reserved.